We reserve all rights in this document and in the information contained therein. Reproduction, use or disclosure to third parties without express authority is strictly forbidden. ©ABB



OUTER TERMINAL



INNER TERMINAL FOR STRANDED CABLE



END SHIELD



SOLID ROD CONNECTOR



The solid rod can be divided either:
Alt.1: 20mm below the bushing flange or
Alt.2: 20mm below the upper end of the bottom porcelain

Bushing Data:

Rated Voltage	170	kV
Phase to Ground Voltage	145	kV
Dry Lightning Impulse 1,2/50µs	650	kV
Wet power frequency AC	275	kV
Routine test 1min dry 50Hz	300	kV
Rated Current	1250	A
Creepage Distance	4080±110	mm
Creepage Distance Protected	1620	mm
Mass	118	kg

Ordering Data:

BUSHING	COLOUR AIR INSULATOR
LF123192-K	BROWN
-L	LIGHT GREY

OUTER TERMINAL

LF 170 002-B	Cu, Ø30, L=125
LF 170 001-B	Al, Ø30, L=125

OTHER TYPES ON REQUEST

INNER TERMINAL FOR STRANDED CABLE

For brazing	Conductor area	DI
LF 170 011-T	up to 285mm²	Ø29
LF 170 011-V	Undrilled with pilot hole	Ø5

SOLID ROD CONNECTOR

LF 170 052 -AD for Alt.1

N/A for Alt.2

ABB Components Ludvika, Sweden

No.					
Ur/Uy		kV Ir		A 50/60 Hz	
LI / SI / AC				kVp	
M	kg	L	mm	V	
C1	pF	Tan δ		%	
C2	pF	Tan δ		%	

Based on	Reg. No.	Title: GOB 650-1250-0 WITH OIL LEVEL GAUGE SHORT END SHIELD	
Prepared: Lövnord	Responsible department: COM/BK		Language
Approved: Johansson	Take over department		
Design engineering review: Hedlund	Database		Page: 1(1)
ABB Components		Document No.: 2751369-217	